



# INUI Directional Wall Pack LIGHT



| description |                         |  |
|-------------|-------------------------|--|
| 1           | Model:                  | INUI-DWP-25                                  |
| 2           | Certification:          | ETL & DLC standard                           |
| 3           | Input voltage:          | AC100-277V/AC180-480V                        |
| 4           | Input frequency:        | 50/60HZ                                      |
| 5           | Consumed power:         | <b>25W to 150W ±5W</b>                       |
| 6           | Power factor:           | >0.9   |
| 7           | Light source:           | Samsung                                      |
| 8           | Luminous flux:          | <b>3000 to 18000lm</b>                       |
| 9           | Light efficacy:         | 110-120lm/W                                  |
| 10          | Colour temperture:      | 3000-6500K                                   |
| 11          | Colour rendering index: | Ra:70-80                                     |
| 12          | Photocell sensor ones   | Fixed type pre-set                           |
| 13          | LED angle:              | Type III, Type V for light distribution lens |



TYPE V



TYPE III  
medium

|    |                     |                     |       |                        |  |                  |
|----|---------------------|---------------------|-------|------------------------|--|------------------|
| 14 | Mount Option        | Wall fixing         |       |                        |  |                  |
| 15 | Shape:              | Square              |       | Packing                |  | Photocell Option |
| 16 | Material:           | aluminium alloy     | 1     | piece in one inner box |  | call for details |
| 17 | Cover colour:       | Black               | size: | 39*33*21cm/ctn         |  |                  |
| 18 | Dimension:          | 370 x 310 x 190mm   |       | GW/NW:3.9kg/3.4kgKG    |  |                  |
| 19 | Net weight:         | 3.4kg/PC            |       | 1 box/ctn              |  |                  |
| 20 | Working temperture: | minus 45 to plus 45 |       | Outdoor                | Outdoor flood lighting,architecture decorated lighting,industrial lighting,physical training centre and outdoor stadium lighting,port,dock etc.Having light distribution system,can be used in street lighting also. |                  |
| 21 | L70:                | >114000 hours       |       |                        |  |                  |